

## 996 Twin Turbo Air Intake Installation Instructions

### 996 Twin Turbo Air Intake System:

1. Remove factory airbox assembly with 13mm socket and Philips screwdriver to remove hose clamps that attach rubber hose to throttle body.
2. Loosen - Phillips screws around airbox housing. Remove stock air box cover.
3. Reinstall stock air filter or BMC air filter or K&N filter.
4. Re-screw Phillips screws into aluminum MAXFLO CUP air box frame. On the left side of the engine bay bottom there is a Rubber bushing that needs to be removed (picture of bushing below); then install our rubber bumper plug into the existing hole that secured the stock airbox. This Fabspeed supplied bumper supports part of the air box. Tighten hose clamps to throttle body and MAF sensor.
5. On 996TT cars slightly loosen the top Phillips screw and slide rain drip edge on back of air box and retighten the screws to clamp it down. The rain drip edge covers the top of the 996TT airbox.

If you have any questions, please contact Fabspeed tech support.

ENJOY YOUR NEW POWER AND SPORTSCAR SOUND. Let us know what you think and visit [WWW.FABSPEED.COM](http://WWW.FABSPEED.COM) for updates and new products for your car.

[info@fabspeed.com](mailto:info@fabspeed.com) 215-646-4945 (9828fax)

