

Bentley Continental GT & GTC Exhaust Installation Instructions

Bentley GT/GTC

1. Enclosed are the parts required to replace any GT/GTC 2ndary undercar catalytic converters and center muffler resonators. Enclosed is an "H" pipe and rear pipes with 2 x exhaust clamps.
2. Using a 13mm socket and wrench and remove 2ndary catalytic converter/center mufflers under the car. The main catalytic converters up at the turbos are unaffected and you CANT get any CEL light.
3. Re-install the new T304SS "H" pipe and rear pipes sections with the 2 x exhaust clamps. Tighten all connections and then DISCONNECT the vacuum line to the exhaust valve located on each of the rear mufflers for maximum power and sports car sound. Plug the flexible vacuum line with a small bolt to seal the vacuum line. You now have the worlds most powerful and cost effective Bentley GT/GTC TWIN TURBO sports exhaust system. ENJOY!

If you have any questions, please contact Fabspeed tech support.

ENJOY YOUR NEW POWER AND SPORTSCAR SOUND. Let us know what you think and visit WWW.FABSPEED.COM for updates and new products for your car.

info@fabspeed.com 215-646-4945 (9828fax)

MOTORSPORT
EXHAUST SYSTEMS • COLD-AIR INTAKES • HEADERS • ECU TUNING

